



User benefits

Simple Installation

- Compact and all in one system, thanks to the oversized integrated dryers.
 Compressed air quality can be improved by the cyclonic water separator and the coalescent filter is available as an option.
- Innovative design
- Easy and fully protected transport
- No special foundation needed

Solid Quality

Outstanding and first-class components:

- Highly reliable transmissions, for a quiet and trouble-free operation.
- High capacity oil/air coolers, perfect air filtration and cooling guarantee less thermal shocks and a longer lifetime.
- Overload protection and full automatic
- High quality and heavy duty motor.

Easy Maintenance and Accessibility

- All service components are located at the front of the machine for excellent accessibility, you just have to open the frontal door for an easy access for service or cleaning, easy access of the coolers, oil filter, separator and air filter replacements.
- Oil-level eye at the front
- Easy and quick check thanks to service door and controller
- Service and cleaning is a one person job

Saving of costs

- Lower energy consumption thanks to IE3 motors or IVR technology
- Optimal efficiency, lubrication and cooling
- Long service intervals

Safety

- Emergency stop
- Protection grid
- IP 54 electrical cubicle
- Internal and external protection for the electric fan.

>>>> RMB 15 - 25 gear driven RMB 15 - 25 IVR direct driven

Compressed air drives your company. Consequently, choosing the right compressor is crucial. Going for our RMB and RMB IVR ranges of highly efficient and flexible oil-injected screw compressors is a choice you will not regret. Bring some fresh air into your company and enjoy the strong performance and high efficiency that come with it.

The new RMB IVR closely follows the air demand by automatically adjusting the motor speed. Combined with the innovative design of direct driven transmission, this results in average energy savings of 35% and an average cut of 25% in the lifecycle cost of a compressor.

>>> Optional and standard features

OPTIONS LIST	Factory
Oil 8000H	✓
Canopy heater *	✓
Food Grade oil	✓
Energy recovery *	✓
Heavy duty inlet filter	✓
Line Filters G + C (with dryer version)	✓
Water separator drain (WSD) with floating drain	✓
Water separator drain (WSD) with automatic drain	V
LD drain for water separator drain (WSD)	✓
Phase sequence relay	std
Wooden crate	V
Graphic controller	✓
Silencing baffle	✓
Connectivity - ICONS box	✓
ES6I multilogic connection with graphic controller	✓

⁼ available



^{*} invalid combination

OUTSTANDING AND FIRST-CLASS COMPONENTS

>>>> RMB 15 - 25 gear driven RMB 15 - 25 IVR direct driven





RMB 18 IVR



- oooling air filter
- 2 emergency stop
- 3 controller4 oil separator
- 5 converter
- air filterair end

- 8 motor
- fan motor
- 10 gear box (FS)
- u direct transmission (IVR)
- 2 coalescent filters
- 13 dryer
- 4 water separator drain



RMB 18 IVR

>>> Energy audit

A frequency driven compressor potentially offers a very energy efficient compressed air installation, with a return on investment of typically 1-2 years. To help you decide to go with a frequency driven compressor or not, MARK has created the Energy Cutter, a tool which calculates in an easy way and visually presents the yearly savings that can be obtained from investing in a frequency driven compressor for any specific industry. Besides the Energy Cutter tool, MARK offers energy audits, specialized advice to make sure you make the right decision when buying your compressor.





SMART TECHNICAL ADVANTAGES








CUSTOMIZE YOUR MACHINES THROUGH A WIDE RANGE OF **OPTIONS:**

- and reduce your energy bill



ES 4000 AS STANDARD ES 4000 ADVANCED AS OPTION FOR ALL THE MODELS



The new direct driven IVR version grants very low specific energy requirements and one of the widest



VERY BIG AIR OIL COOLER AND OPTIMIZED AIR FLOW

TECHNICAL DATA - RMB 15 - 25 (IVR)



>>> Fixed speed

FIXED SPEED	Pres	Max. Working Free Air Delivery @ Pressure reference conditions*					Motor	Power	Noise Level	Weight			
Model				Ţ	,		H	•	•	≜ kg			
	BAR	PSI	m ³ /h	l/s	l/min	cfm	kW	hp	dB(A)	FM	FM D	500L D	
	7,5	109	162	44,9	2696	95		15 20			375	550	
RMB 15	8,5	123	152	42,3	2536	90	15		67	330			
HIVID 13	10	145 136 37,8 2266 80	20	07	330	0/0	550						
	13	189	117	32,4	1946	69							
	7,5	109 199 55,3 3317 117											
RMB 18	8,5	123	189	52,4	3144	111	18,5	25	68	355	405	580	
TIME 10	10	145	175	48,7	2922	103	10,0	20	00				
	13	189	137	38,0	2279	80							
	7,5	109	231	64,3	3858	136				370	420		
RMB 21	8,5	123	224	62,4	3741	132	22	30	69			595	
NWD 21	10	145	198	54,9	3294	116		30	03	370	420		
	13	189	167	46,5	2790	99							
	7,5	109	253	70,2	4210	149					435		
RMB 25	8,5	123	239	66,4	3987	141	26	35	71	385		610	
NIVID 25	10	145	224	62,1	3728	132	20	55	' '	300	430		
	13	189	196	54,4	3263	115							

^{*} Unit performance measured according to ISO 1217, Annex C, latest edition

>>> Variable speed

VARIABLE SPEED	worl pres	Min. working pressure		Max. working pressure		Free Air Delivery @ reference conditions * Win FAD * Max. FAD *										otor wer	Noise level **		Weigh						
Model	Bar	PSI	Bar	PSI		7 bar			7 bar			3,5 ba l/s			9,5 ba			12,5 bar m ³ /h l/s l/min		kW	hp	dB(A)	FM	FM D	500L D
RMB 15 IVR	5,5	80	13	189	47	13	780	175	48,5	2911	157	43,7	2620	149	41,5	2489	128	35,6	2138	15	20	68	310	355	530
RMB 18 IVR	5,5	80	13	189	47	13	780	210	58,4	3505	194	53,8	3225	182	50,5	3029	146	40,6	2435	18,5	25	70	325	375	550
RMB 21 IVR	5,5	80	13	189	47	13	780	235	65,3	3920	216	60,1	3606	203	56,4	3386	182	50,5	3029	22	30	71	330	385	560
RMB 25 IVR	5,5	80	13	189	47	13	780	249	69,3	4158	233	64,8	3891	225	62,4	3742	196	54,5	3267	26	35	72	350	400	575

^{*} Unit performance measured according to ISO 1217, Annex C, latest edition ** Noise level measured according to ISO2151:2004 using ISO 9614/2

>>> Dimensions

	DIMENSIONS							
Model Fixed + Variable speed	Length mm	Width mm	Height mm					
Floor Mounted	1200	835	1220					
Floor Mounted + Dryer	1450	835	1220					
500L - Dryer	1940	835	1835					



^{**} Noise level measured according to ISO 2151:2004 using ISO 9614/2

^{***} Reference working pressure: $\overline{7}$ - 8 - 9,5 - 12,5 bar

Oil injected screw compressors, gear and direct driven

RMB 15 - 25 (IVR)





- A high quality product offering you technology you can trust.
- Our products are easy to use and guarantee high reliability.
- Distributors are always nearby ensuring availability of both products and support.
- Choosing our high performance products entails a partnership that will boost your business.
- · Safeguarding long-term productivity through optimal serviceability and use of original parts.



Care. Trust. Efficiency.

Care.

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

Trust.

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

Efficiency.

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

© 2019, Mark. All rights reserved. All mentioned brands, product names, company names, trademarks and service marks are the properties of their respective owners. Our products are constantly being developed and improved. We thus reserve the right to modify product specifications without prior parties Directors are not contracted by indicated.

5999200470