>>>> RMB 22 - 37 kW RMB IVR 22 - 37 kW

> Solid, simple, smart: Advanced reliability in compressed air

> > RIK



ITY

11

M

# 



## User benefits

#### Simple Installation

- Compact and all in one system, thanks to the oversized integrated dryers. Compressed air quality can be improved by the cyclonic water separator and the coalescent filter is available as an option.
- Innovative design
- Easy and fully protected transport
- No special foundation needed

## Solid Quality

Outstanding and first-class components:

- Highly reliable transmissions, for a quiet and trouble-free operation.
- High capacity oil/air coolers, perfect air filtration and cooling guarantee less thermal shocks and a longer lifetime.
- Overload protection and full automatic control.
- High quality and heavy duty motor.

# Easy Maintenance and Accessibility

- All service components are located at the front of the machine for excellent accessibility, you just have to open the frontal door for an easy access for service or cleaning, easy access of the coolers, oil filter, separator and air filter replacements.
- Oil-level eye at the front
- Easy and quick check thanks to service door and controller
- Service and cleaning is a one person job

## Saving of costs

- Lower energy consumption thanks to IE3 motors or IVR technology
- Optimal efficiency, lubrication and cooling
- Long service intervals

#### Safety

- Emergency stop
- Protection grid
- IP 54 electrical cubicle
- Internal and external protection for the electric fan.

## >>>> RMB 22-37 Gear driven RMB 22-37 IVR Direct driven

Compressed air drives your company. Consequently, choosing the right compressor is crucial. Going for our RMB and RMB IVR ranges of highly efficient and flexible oil-injected screw compressors is a choice you will not regret. Bring some fresh air into your company and enjoy the strong performance and high efficiency that come with it.

The new RMB IVR closely follows the air demand by automatically adjusting the motor speed. Combined with the innovative design of direct driven transmission, this results in average energy savings of 35% and an average cut of 25% in the lifecycle cost of a compressor.

## >>> Optional and standard features

| OPTIONS LIST  | Factory               | Sales                 |  |  |  |  |
|---|-----------------------|-----------------------|--|--|--|--|
| OIL 8000H   | <ul> <li>✓</li> </ul> | ×                     |  |  |  |  |
| CANOPY HEATER   | V                     | <ul> <li>✓</li> </ul> |  |  |  |  |
| FOOD GRADE OIL  | <ul> <li>✓</li> </ul> | ×                     |  |  |  |  |
| OPTION ENERGY RECOVERY                                    | V                     | <ul> <li>✓</li> </ul> |  |  |  |  |
| HEAVY DUTY INLET FILTER                                   | 🖌 std on 30 and 37 kW | 🖌 std on 30 and 37 kW |  |  |  |  |
| COALESCENCE FILTER OPTION<br>0,1 ppm residual oil content | (with dryer)          | (with dryer)          |  |  |  |  |
| WATER SEPARATOR DRAIN<br>(WSD) + automatic drain          | ~                     | v                     |  |  |  |  |
| PHASE SEQUENCE RELAY                                      | std                   | std                   |  |  |  |  |
| TROPICAL THERMOSTAT                                       | std                   | std                   |  |  |  |  |
| WOODEN PACKAGE  | <ul> <li>✓</li> </ul> | ×                     |  |  |  |  |
| ES 4000 advanced controller                               | <ul> <li>✓</li> </ul> | ×                     |  |  |  |  |
| Main isolator SWITCH                                      | V                     | ×                     |  |  |  |  |
| Silencing baffle  | <ul> <li>✓</li> </ul> | <ul> <li>✓</li> </ul> |  |  |  |  |





## >>> SMART TECHNICAL ADVANTAGES







#### **CUSTOMIZE YOUR MACHINES** THROUGH A WIDE RANGE OF OPTIONS:

- Canopy heaters for low temperature installation



ES 4000 AS STANDARD ES 4000 ADVANCED AS OPTION FOR ALL THE MODELS



#### THE ENERGY CUTTER:

#### VERY BIG AIR OIL COOLER AND **OPTIMIZED AIR FLOW**



## YOUR ENERGY EFFICIENT AND SOLID PERFORMANCE

## >>> RMB 22 - 37 gear driven RMB 22 - 37 IVR direct driven

RMB 37 IVR D



4 oil separator (30 - 37 kW) 5 oil separator (22 - 26 kW) 6 electrical cubicle 🗾 converter 🛽 air filter





#### **RMB 26 D**

### >>>> Energy audit

A frequency driven compressor potentially offers a very energy efficient compressed air installation, with a return on investment of typically 1-2 years. To help you decide to go with a frequency driven compressor or not, MARK has created the Energy Cutter, a tool which calculates in an easy way and visually presents the yearly savings that can be obtained from investing in a frequency driven compressor for any specific industry. Besides the Energy Cutter tool, MARK offers energy audits, specialized advice to make sure you make the right decision when buying your compressor.





## >>> Fixed speed

| FIX<br>SPEED | Max. Working<br>Pressure | Reference<br>Working<br>Pressure | Motor | Power |                   | e Air Delivery<br>rence conditio |     | Noise<br>Level<br>** | Cooling Air<br>flow | We      | eight |
|--------------|--------------------------|----------------------------------|-------|-------|-------------------|----------------------------------|-----|----------------------|---------------------|---------|-------|
|              | 0                        | 0                                | H     | Þ     |                   | Ť                                |     |                      | 4                   | FM      | FM D  |
| Model        | BAR                      | PSI                              | kW    | hp    | m <sup>3</sup> /h | l/s                              | cfm | dB(A)                | m³/h                | <b></b> | 🔒 kg  |
|              | 7,5                      | 109                              |       |       | 232               | 65                               | 137 |                      |                     |         |       |
| RMB 22*      | 8,5                      | 123                              |       | 30    | 219               | 61                               | 129 | 68                   | 2300                | 445     | 520   |
| RIVID 22"    | 10                       | 145                              | H     | 30    | 199               | 55                               | 117 | 00                   | 2300                | 440     | 320   |
|              | 13                       | 189                              |       |       | 172               | 48                               | 101 |                      |                     |         |       |
|              | 7,5                      | 109                              |       |       | 271               | 75                               | 160 | 69                   |                     | 460     |       |
| RMB 26       | 8,5                      | 123                              | 26    | 26 35 | 258               | 72                               | 152 |                      | 4800                |         | 535   |
| NIMD 20      | 10                       | 145                              | 20    | 30    | 236               | 66                               | 139 | 09                   | 4600                | 400     | 000   |
|              | 13                       | 189                              |       |       | 205               | 57                               | 120 |                      |                     |         |       |
|              | 7,5                      | 109                              |       |       | 328               | 91                               | 193 |                      |                     |         |       |
| RMB 30       | 8,5                      | 123                              | 30 40 | 300   | 83                | 177                              | 70  | 4800                 | 560                 | 681     |       |
| RIVID 30     | 10                       | 145                              | 30    | 40    | 275               | 76                               | 162 | 70                   | 4000                | 560     | 001   |
|              | 13                       | 189                              |       |       | 240               | 67                               | 141 |                      |                     |         |       |
|              | 7,5                      | 109                              |       |       | 367               | 102                              | 216 |                      |                     |         |       |
| RMB 37       | 8,5                      | 123                              | 27    | 50    | 339               | 94                               | 199 | 71                   | 4800                | 623     | 744   |
|              | 10                       | 145                              | - 37  | 00    | 304               | 84                               | 179 | 1                    | 4800                | 023     | / 44  |
|              | 13                       | 189                              |       |       | 275               | 76                               | 162 |                      |                     |         |       |

\* Available only 400 V 50Hz - IEC - CE

## >>> Variable speed

| VARIABLE<br>SPEED | Min. working<br>pressure |           | Motor p |    | Free Air Delivery @ reference conditions * |      |                   |     |                   |     |                   |     |                   | Cooling<br>air flow |       |                   |     |      |
|-------------------|--------------------------|-----------|---------|----|--|------|-------------------|-----|-------------------|-----|-------------------|-----|-------------------|---------------------|-------|-------------------|-----|------|
|                   |                          |           |         |    | Min F/                                     | AD * | Max. FAD *        |     |                   |     |                   |     |                   |                     |       |                   |     |      |
|                   | ()                       |           |         | P  | 7 ba                                       | ar   | 4 bi              | ar  | 7 b               | ar  | 9,5               | bar | 12,5              | bar                 |       | 4                 | FM  | FM D |
| Model             | BAR / PSI                | BAR / PSI | kW      | hp | m <sup>3</sup> /h                          | l/s  | m <sup>3</sup> /h | l/s | m <sup>3</sup> /h | l/s | m <sup>3</sup> /h | l/s | m <sup>3</sup> /h | l/s                 | dB(A) | m <sup>3</sup> /h |     | kg   |
| RMB 22 IVR*       | 5,5-80                   | 13-188    | 22      | 30 | 46   | 13   | 250               | 69  | 243               | 68  | 211               | 59  | 176               | 49                  | 68    | 2300              | 434 | 503  |
| RMB 26 IVR        | 5,5-80                   | 13-188    | 26      | 35 | 46   | 13   | 290               | 81  | 277               | 77  | 247               | 69  | 205               | 57                  | 69    | 4800              | 444 | 513  |
| RMB 30 IVR        | 5,5-80                   | 13-188    | 30      | 40 | 60   | 17   | 348               | 97  | 327               | 91  | 289               | 80  | 243               | 68                  | 70    | 4800              | 492 | 607  |
| RMB 37 IVR        | 5,5-80                   | 13-188    | 37      | 50 | 64   | 18   | 380               | 106 | 360               | 100 | 325               | 90  | 265               | 74                  | 71    | 4800              | 514 | 629  |

\* Available only 400 V 50Hz - IEC - CE

## >>> Dimensions

|                  | DIMENSIONS  |              |                     |                                |  |  |  |  |  |  |
|------------------|-------------|--------------|---------------------|--------------------------------|--|--|--|--|--|--|
| Model            | width<br>mm | height<br>mm | length<br>IVR<br>mm | lenght<br>IVR +<br>dryer<br>mm |  |  |  |  |  |  |
| RMB 22<br>RMB 26 | 000         | 1555         | 1000                | 1320                           |  |  |  |  |  |  |
| RMB 30<br>RMB 37 | 830         | 1555         | 1320                | 1810                           |  |  |  |  |  |  |



Oil injected screw compressors, gear and direct driven

RMB and RMB IVR





- A high quality product offering you technology you can trust.
- Our products are easy to use and guarantee high reliability.
- Distributors are always nearby ensuring availability of both products and support.
- Choosing our high performance products entails a partnership that will boost your business.
- Safeguarding long-term productivity through optimal serviceability and use of original parts.



# Care. Trust. Efficiency.

#### Care.

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

#### Trust.

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

#### Efficiency.

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.