

Solid, simple and smart: advanced reliability in compressed air RMM 30 - 45 / RMM IVR 30 - 45





RMM 30 - 45 RMM 30 - 45 IVR

Your production relies on compressed air, so you know the value of a compressor you can always count on. The RMM was built to be your no-hassle, zero-frustration work floor companion. While typically compressors in this segment are belt-driven, our newest oil-injected rotary screw compressor comes with a direct gear transmission. That means no belts to tension, maintain and replace. The RMM also features an advanced controller with integrated connectivity to easily manage and monitor your compressed air system. The result: reliability, ease-of-use and limited maintenance from the very first moment you commission your new RMM.



1. Simple installation, easy to use

- Plug-and-play installation
- No special foundation required
- Small footprint
- Ready-to-use, integrated dryer
- Intuitive controller

 \square



2. Increased productivity, reliable operations

- No downtime for belt tensioning or replacement
- Quiet and smooth gear transmission
- Low noise level
- High-capacity oil/air coolers and perfect air filtration ensure a long lifetime
- Unbeatable performance with heavy-duty IP55 motors



3. Connectivity for performance and reliability

- Remote connectivity, anywhere, any time
- Notifications and shutdown alarms eliminate risk of downtime
- Increased reliability with planned service interventions

5. Less maintenance, no-hassle service

- Quick oil level check through front panel gauge

- Easy access to service components

Service becomes a one-person jobService plans tailored to your needs

- Cost optimization advice

4. Advanced cost savings

- 3% savings versus traditional
- belt-driven transmissions
- IE3 motor as standard
- Variable Speed version available for 35% energy savings





More value for money

With the RMM, we set out to build the better, more reliable compressor on the market. The compressor offers some major innovations that will you give a lifetime of value and savings.

A highly reliable gear transmission

A belt-driven compressor has a higher risk of downtime and maintenance-related costs. Unscheduled belt tensioning and replacement cause productivity losses and there is always the risk of post-service belt misalignment. That is why the RMM comes with a gear drive transmission. You have no belts to replace and enjoy lower operating (service) costs. What is more, the RMM is 3% more energy efficient compared to belt-driven compressors.







ES4000S controller for optimal performance

The new RMM comes standard equipped with an ES4000S controller that manages and monitors compressor performance. Easy to use, the ES4000S and the optional ES4000T with touch screen give you compressor updates and service alerts before they become a problem. The integrated **CONS** connectivity gives you the advanced benefits of remote monitoring and management:


- Remote monitoring that helps you optimize your compressed air system and save energy.
- On-time maintenance to optimize costs and ensure a longer machine life.
- Potential problems are recognized before they can pose a threat to the continuity of your production.

VSD: double digit energy savings

Is your work floor always running at 100%? A traditional compressor is, even when you don't need its full capacity. For most production environments, compressed air use fluctuates during the day or week.

That is why the RMM offers optional variable speed drive technology. A

RMM with VSD matches its air delivery to your actual need. That means it is not using – and wasting – energy when your demand for compressed air is lower. Ask your Mark representative to calculate how much you can save with a RMM VSD. Typically, energy savings run in the double digits!





A total solutions offering from Mark

Line Filters

Eliminate oil and dust from the compressed air to avoid the risk of contamination of your air system and final products.

Air Receiver

Buffer storage for your compressed air helps with condensate separation, pressure stabilization and efficient compressor operation.

Oil-Water Separator

Our oil-water separator captures compressor condensate and separates the oil for safe disposal.


AIRnet

Our easy-to-install piping system distributes your compressed air with maximum efficiency and reliability.

Dryers

You need your compressed air to be dry and clean to protect your pneumatic tools and final products. Mark offers a range of reliable, highperformance dryers to meet your air quality requirements and air system specifications.





- 1. Pre-filter
- 2. Oil separator
- 3. Electrical cubicle
- 4. Converter
- 5. Air filter
- 6. Air end
- 7. Motor
- 8. Fan motor
 9. Gear box
- 10. Dryer
- 11. Oil-sight glass & oil-refill
- 12. Oil-filter

Optional features

Of course, one size does not fit all.

A range of options is available to tailor your RMM to your specific requirements and production environment.

- Oil 8000h
- Canopy heater
- Food grade oil
- Coalescence filter optionWater separator drain + automatic drain
- Wooden package

- ES4000T controller
- Main isolator switch
- ECO6i central control



Technical specifications

Fixed speed

	Max. working	Reference	Motor Power		Free Air Delivery @ reference conditions			Noise	Cooling Air flow	Weight	
	pressure	working pressure						Level		FM	FMD
Model	bar	bar	kw	hp	m³/h	l/s	cfm	dB(A)	m³/h	kg	kg
RMM 30	7.5	7	30	40	320	89	189	71.5	4800	589	707
	8.5	8			310	86	182				
	10	9.5			274	76	161				
RMM 37	7.5	7	37	50	396	110	233	73	4800	610	728
	8.5	8			365	102	215				
	10	9.5			342	95	201				
RMM 45	7.5	7	45	60	454	126	267	74.5	6700	629	747
	8.5	8			436	121	256				
	10	9.5			400	111	235				

Variable speed

	Min. working	Max. working	Motor Power		Free Air Delivery @ reference conditions						Weight	
					Min.FAD*	Min.FAD* Max. FAD*				Cooling Air flow	FM	FMD
	pressure	pressure			7 bar	7 bar 8 bar		9,5 bar				TIME
Model	bar	bar	kW	hp	m³∕h I∕s cfm	m³∕h I∕s cfm	m³∕h I∕s cfm	m³∕h I∕s cfm	dB(A)	m³∕h	kg	kg
RMM 30 IVR	4	10	30	40	85 24 50	318 88 187	306 85 180	274 76 161	71.5	4800	605	723
RMM 37 IVR	4	10	37	50	109 30 64	401 111 236	370 103 218	343 95 202	73	4800	626	744
RMM 45 IVR	4	10	45	60	110 31 65	447 124 263	434 121 255	404 112 238	74.5	6700	656	774

*400 V 50Hz - IEC - CE



Contact your local representative:

www.mark-compressors.com

CARE

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

TRUST

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

EFFICIENCY

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

© 2020, Mark. All rights reserved. All mentioned brands, product names, company names, trademarks and service marks are the properties of their respective owners. Our products are constantly being developed and improved. We thus reserve the right to modify product specifications without prior notice. Pictures are not contractually binding.

